

MATERIAL SAFETY DATA SHEET

MSDS Number: 04 October 2012

1. PRODUCT IDENTIFICATION

PRODUCT NAME : Lithium Ion batteries

UN NO.: 3480

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	CONTENT	CAS No.	EINECS
	(% of tot. weight)		
Lithium Iron	50%	15365-14-7	NA
Phosphate Carbon			
coated (LiFePO4)			
Carbon(Graphite)	10%	7782-42-5	231-955-3
PP	5%	9003-07-0	NA
PVDF	2%	24937-79-9	NA
PE	5%	9002-88-4	NA
CMC	0.5%	9004-32-4	NA
LiPF6	5%	21342-40-3	244-334-7
EC	5%	96-49-1	202-510-0
DMC	5%	616-38-6	210-478-4
Ni	2.5%	7440-02-0	231-111-4
Cu	5%	7440-50-8	231-159-6
A1	5%	7429-90-5	231-072-3

3. HAZARDS/HEALTH IDENTIFICATION

Intact batteries present no specific hazards. If batteries show signs of leaking, AVOID skin or eye contact with the material leaking from the battery. If battery is burning, put out the fire by using right extinguisher.

Potential Health Hazards:

Eye: no particular hazards for proper use. It will cause severe irritation or chemicalburns when batteries are broken.

Skin: no particular hazards for proper use. It will cause skin severe irritation by inhalation of EC and DMC or chemicalburns when batteries are broken.

Inhalation: it will irrite breath system by being exposed to fumes when batteries are broken.

Ingestion: it is deleterious by swallowing battery. Broken batteries will cause severe chemicalburns to mouth, esophagus and gastroenteric system.

Environment hazards: It will cause different harms to man and entironment.

Burning and exploding hazards: when the battery is short-circuited, over charged or over heated, it may cause electrolyte of the bttery leaked oute or the battery exploding.

DC AFAM NV Venecoweg 20A B-9810 Nazareth Tel +32 9 243 73 90 fax +32 9 273 43 95 1



4. FIRST-AID MEASURES

Skin Contact: wash the affected area for at least 15-30 minutes with clean water, and seek medical attention immediately.

Eye contact: wash the affected area with clean water, and seek medical attention immediately. **Inhalation:** move to the drafty place, wash oral cavity and nasal cavity, and seek medical attention immediately.

Ingestion: if the sufferer is conscious, feed him/her some water and milk, please not urge him/her to vomit, and seek medical attention immediately.

5. FIRE-FIGHTING MEASURES

Hazard properties: the battery may be over-heated by outside and interior short-circuit, and burning batteries may emit toxic fumes.

Hazardous Combustion products: metallic oxide, Carbon oxide (CO), Carbon dioxide (CO2), etc. **Extinguishing Media:** species D fire extinguishers of chemical dry powder, yellow sands. Do not use water.

Firemen safeguard: firemen should wear fire-fighting suits with a self-contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURE

General information: employ proper protection establishment according to directions of part.8. **Splash/leakage**: remove the source of fire and heat. Collect the leaked battery and place it into appropriate vessel for reclaiming and discarding according to correlative native and local laws, regulations and environmental protection requirements. Avoid vibration and physical damage. Isolate irrelative personnels.

7. HANDLING&STORAGE

Handling:

- Do not vibrate the battery excessively.
- Avoid short-circuiting the battery. Though short-circuit for little time will not influence badly the battery, shortcircuit for long time will lose the battery's energy and bring plenty of heat which will burn skin and cause fire or explosion indeed.
- The equipments of metal which are used for battery pack such as coin, metal accounterments, metal worktable, metal strip, etc. are source of short-circuit.
- It should be provide with effective measures to prevent short-circuit during transportation and storage.
- Do not disassemble and damage the battery.
- The battery should be transported with 10-50% charged states.
- Do not contact the battery with water.
- Do not store the battery in the place with point-blank sunshine.

Storage:

- The battery should be 40-60% charged for long time storage.
- The battery should be stored in the place where is cool, dry and lee.
- High temperature may cause the battery capability loss, leakage and rustiness.



- Do not expose the battery to fire.
- Store the battery away from moisture

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

Engineering control: No information available.

Sanitation measure: no special requirements for handling the battery well packed. **Respiration protection:** no special requirements for handling the battery well packed.

Eye protection: no special requirements for handling the battery well packed. **Body protection:** no special requirements for handling the battery well packed.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance and character: solid

Color: aluminous white

Odor: no

Voltage: 2.75 — 48 V Weight: 10 — 4000g

Capacity: 100 — 40000 mAh Function: power supply

10. STABILITY &REACTIVITY

Stability: stable for normal usage.

Incompatibility (Materials to avoid): electric materials, water, seawater, oxidant, acid.

Conditions to Avoid: short-circuit, collision, refit, high temperature (over 100°C), point-blank

sunshine and high humidity environment.

Decomposition products: toxic gas brought when burning.

Hazardous polymerization: not occur.

11. TOXICOLOGICAL INFORMATION

CAS NO°	RETCS
15365-14-7	None list
7782-42-5	MD9659600
9003-07-0	UD1842000
24937-79-9	None Listed
9002-88-4	TQ3325000; KX3270000
9004-32-4	FJ5950000
21342-40-3	None Listed
96-49-1	FF9550000
616-38-6	FG0450000
7440-02-0	QR5950000;QR6126100;QR6555000;QR7120000
7440-50-8	GL5325000;GL7440000;GL7590000
7429-90-5	BD0330000;BD1020000



Acute toxicity:

Ingredients: hydroxide methyl cellulose sodium

LC50 : >5800 mg/m3/4h (small rat,inhalation)

LD50 : >27 g/kg (small rat, to eat)

Ingredients: LiPF6

• LD50 : >1702 mg/kg (big rat, by mouth)

Ingredients: Ethylene carbonate

LD50 : >10000 mg/kg (big rat, by mouth)
 LD50 : >3000 mg/kg (rabbit,by skin)

Ingredients: Dimethyl carbonate

LD50 : >6000 mg/kg (small rat, by mouth)
 LD50 : >13000 mg/kg (big rat, by mouth)

Irritation: NA
Carcinogenicity:
Ingredients: nickel

LARC-2B: potential carcinogenACGIH A5:non-human carcinogen

Other substances: not be listed under ACGIH, IARC, NTP

12. ECOLOGICAL INFORMATION

Ecological toxicity: the chemicals of the battery will cause harm to the environments if it is

discarded to the surroundings.

Biodegradability: No information available. **Non-biodegradability**: No information available.

13. DISPOSAL

Disposal means: according to correlative national and local laws and regulations.

14. TRANSPORT INFORMATION

According to the correlative regulations of IATA DGR – 53rd Edition.

Not Restricted, PI 965 Section II

According to the correlative regulations of IMDG CODE.

Not Restricted, SP 188

According to the correlative regulations of ADR 2009 Reglementation.

Not Restricted, SP 188

DC AFAM NV Venecoweg 20A B-9810 Nazareth Tel +32 9 243 73 90 fax +32 9 273 43 95 4



15. REGULATORY INFORMATION

The regulations following are specifically applied to the safe usage, production, storage, transport and load and unload for dangerous chemicals.

_

The Regulations of Safe Management Regarding Dangerous Chemicals (issued by State Council at Jan. 26, 2002)

_

The Rules of implementation of Safe Statute Regarding Dangerous Chemicals (No.667,1992)

_

The Regulations of Safe Use of Dangerous Chemicals in Workplace(No.423,1992)

16. OTHER INFORMATION

Creation Date: Oct. 22, 2012

Revision explanation:

The informations of this MSDS which represents the best information currently available to us, are just to describe the requirements regarding health, safety and environment of the product and provided to you just for referrence and consideration. Some measures of this MSDS is not the only. we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.