Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 1 of 19

	Section 1: Identification of the substance/mixture and of the company/undertaking Product Identifier
1.1.1	Trade name/designation:
1.1.1	Dry Charge Battery
1.2	Relevant identified uses of the substance or mixture and uses advised against
1.2.1	Relevant identified uses:
1.2.1	Power sport batteries
1.2.2	Uses advised against:
1.2.2	Any other not listed above
12	
	Details of the supplier
1.3.1	Supplier:
	Yuasa Battery, Inc.
1.3.2	Website
	www.yuasabatteries.com
1.3.3	Information contact
	2901 Montrose Ave.
	Laureldale, PA 19605
	United States
1.3.4	National contact
	Yuasa Battery Environmental Resources: (610)929-5781
1.4	Emergency Telephone Number
	CHEMTREC: Domestic (800)424-9300
	International: 1(703)527-3887

Section 2: Hazards identification


Material is an article. No health effects are expected related to normal use of this product as sold. Hazardous exposure can occur only when the product is heated, oxidized or otherwise processed or damaged to create lead dust, vapor or fume. Refer to the Material Safety Data Sheet for Lead Acid Battery when battery is filled with electrolyte/battery acid.

2.1 Classification of the substance or mixture: 2.1.1 Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] Class 13: Non-flammable solids in non-flammable package 2.1.2 Classification according to 67/548/EEC or 1999/45/EC Xi: Irritating 2.2 Label elements 2.2.1 Labeling according to Regulation (EC) No 1272/2008 Product identifier: Dry Charge Battery Hazard pictograms: Xi: Irritating

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 2 of 19



Symptoms of lead toxicity include headache, fatigue, abdominal pain, loss of appetite, muscular aches and weakness, sleep disturbances and irritability. Lead absorption may cause nausea, weight loss, abdominal spasms, and pain in arms, legs and joints.

Effects of chronic lead exposure may include central nervous system (CNS) damage, kidney dysfunction, anemia, neuropathy particularly of the motor nerves with wrist drop, and potential reproductive effects.

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 3 of 19

	Section 3: Composition/information on ingredients							
3.1 Des	3.1 Description of the mixture:							
CAS No	EC No	% [weight]	Name	WHMIS Classifications	Classification according to CLP (1272/2008)			
7439-92-1	231-100-4	89-92%	Lead	D2A	Xn, N, T; R20/22, R33, R50, R50/53, R53, R61, R62; Repr. Cat. 1, Repr. Cat. 3; S53, S45, S60, S61 except those specified elsewhere in the annex			
7440-36-0	231-146-5	0.2%	Antimony	Uncontrolled product according to WHMIS classification criteria; D1B(powder)	Xn, N; R20/22, R51/53; S2, S61 except tetroxide, pentoxide, trisulphide, pentasulphide, and those specified elsewhere in the annex			
7440-31-5	231-141-8	0.006%	Tin	Uncontrolled product according to WHMIS classification criteria	Not Listed			
7440-38-2	231-148-6	0.003%	Arsenic	D1A, D2A	T, N; R23/25, R50/53; S1/2, S20/21, S28, S45, S60, S61			
7440-70-2	231-179-5	0.002%	Calcium	B6, E	F; R15; S2, S8, S24/25, S43			

Case material composes 5-6% of the article. Case material includes the following components: 1-Propene, homopolymer (9003-07-0); Polystyrene (9003-53-6); Acrylonitrile, polymer with styrene (9003-54-7); Acrylonitrile, polymer with 1,3-butadiene and styrene (9003-56-9); Styrene polymer with 1,3-butadiene and styrene (9003-56-9); Styrene polymer with 1,3-butadiene (9003-56-9); Styrene polymer with 1,3-butadiene (Kraton) (9003-55-8); Ethylene, chloro-, polymer (9003-86-2); Hard Rubber; Polycarbonate; Polyethylene.

Section 4: First Aid Measures

4.1 Description of first aid measures

- 4.1.1 Eye contact: First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If contact with material occurs flush eyes with water. If signs/symptoms develop, get medical attention.
 4.1.2 Inhalation:
 - First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If signs/symptoms develop, move person to fresh air.
- 4.1.3 Skin contact: First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. Wash skin with soap and water. If signs/symptoms develop, get medical attention.

4.1.4 Ingestion: First aid is not expected to be necessary if material is used under ordinary conditions and as recommended. If ingested consult physician immediately.

4.1.5 Self-protection of the first aider:

If artificial respiration is required use a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 4 of 19

Extinguishing media:
Suitable extinguishing media:
CO2, dry chemical or foam
Unsuitable extinguishing media:
Avoid using water
Special hazards arising from the substance or mixture
Hazardous combustion products:
Lead portion of battery will likely produce toxic metal fume, vapor or dust.
Advice for fire-fighters:
Keep sparks or other sources of ignition away from batteries. Do not allow metallic materials to
simultaneously contact negative and positive terminals of cells and batteries.
Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective
clothing will only provide limited protection.
Additional information:
Material itself is non-combustible although in fire situations will likely produce toxic metal fume, vapor or
dust.
Section 6: Accidental release measures
Personal precautions, protective equipment and emergency procedures
No special precautions expected to be necessary if material is used under ordinary conditions and as
recommended. Avoid contact of lead with skin.
For non-emergency personnel
Protective equipment:
Wear chemical gloves
For emergency responders
No emergency procedures are expected to be necessary if material is used under ordinary
conditions as recommended. Use normal clean up procedures.
Personal protective equipment:
Wear chemical gloves, goggles, acid resistant clothing and boots, respirator if insufficient
ventilation. Environmental precautions:
Prevent entry into waterways, sewers, basements or confined areas. Runoff from fire control and dilution
water may be toxic and corrosive and may cause adverse environmental impacts.
Methods and material for containment and cleaning up
For containment:
Lead dust should be vacuumed or wet swept into a D.O.T. approved container. Use controls that minimize
fugitive emissions. Do not use compressed air.
For cleaning up:
Contact local and/or state officials for proper disposal requirements.
contact total and/or state officials for proper disposal requirements.

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 5 of 19

Section 7: Handling and storage Precautions for safe handling 7.1.1 Protective measures: Handle batteries cautiously. Do not tip to avoid spills (if filled with electrolyte). Avoid contact with internal components. Wear protective clothing when filling or handling batteries. Follow manufacturer's instructions for installation and service. Do not allow conductive material to touch the battery terminals. Short circuit may occur and cause battery failure and fire. 7.1.2 Advice on general occupational hygiene Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Eyewash stations and safety showers should be provided with unlimited water supply. Handle in accordance with good industrial hygiene and safety practice. 7.2 Conditions for safe storage, including any incompatibilities Avoid contact with strong bases, acids, combustible organic materials, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen, reducing agents and water. Technical measures and storage conditions:

Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Batteries should be stored under roof for protection against adverse weather conditions. Place cardboard between layers of stacked batteries to avoid damage and short circuits. Store batteries on an impervious surface. Storage class:

Class 13: Non-flammable solids in non-flammable package

	Section 8: Exposure controls/personal protection					
8.1Control parame8.1.1Occupational ex						
Limit value type (country of origin)	Substance name	EC-No.	CAS-No	Limit value	Monitoring and observation processes	
TWA(ACGIH USA) STEL (CA-ON) TWA (CA-ON) TWA (CA-QU) STEL (CH) TWA (CH) TWA (CH) Biological Limit Value (FI) TWA (ME) Ceiling (NIOSH)	Arsenic		7440-38-2	0.01 mg/m3 50 μg/m3 10 μg/m3 1.1 mg/m3 1.2 mg/m3 0.01 mg/m3 0.01 mg/m3 70 nmol/L 1.1 mg/m3 1.2 mg/m3	Designated substance regulation Medium: Urine Time: end of shift at end of workweek	
TWA(ACGIH USA) TWA (CA) TWA (CA) TWA (FI) STEL(ME) TWA (ME) TWA (ME) TWA (NIOSH USA) STEL (CH) TWA (CH) TWA (ACGIH USA) TWA (CA)	Tin Antimony	231-141-8 231-146-5	7440-31-5 7440-36-0	2 mg/m3 2 mg/m3 2 mg/m3 2 mg/m3 4 mg/m3 2 mg/m3 2 mg/m3 1.5 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3		

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 6 of 19

TWA (FI) TWA (JP) TWA(ME) TWA(NIOSH USA) TWA (OSHA USA)				0.5 mg/m3 0.1 mg/m3 0.5 mg/m3 0.5 mg/m3 0.5 mg/m3	
TWA (ACGIH) TWA(CA ON) TWA(CA QU) STEL(CH) TWA(CH) TWA(FI) Biological Limit Value (FI) TWA(JP) TWA(ME) TWA(ME) TWA(NIOSH) TWA(OSHA)	Lead	231-100-4	7439-92-1	0.05 mg/m3 0.05 mg/m3 0.05 mg/m3 0.15 (0.09) mg/m3 0.05(0.03)mg/m3 0.1 mg/m3 1.4 umol/L 0.1 mg/m3 0.15 mg/m3 0.05 mg/m3 50 ug/m3	Designated substance regulation Dust (fume) Dust (fume) Dust As Pb, dust and fume

- 8.2 Exposure controls
- 8.2.1 Appropriate engineering controls:
 - Store and charge in a well-ventilated area. General dilution ventilation is acceptable.
- 8.2.2 Personal protective equipment:
- 8.2.2.1 Pictograms:



- 8.2.2.2 Eye/Face protection:
 - Wear protective eyewear (goggles, face shield or safety glasses with side shields).
- 8.2.2.3 Skin protection:
 - Wear appropriate gloves.

Physical state: Solid

No skin protection is ordinarily required under normal conditions of use. In accordance with industrial hygiene practices, if contact with leaking battery is expected precautions should be taken to avoid skin contact. Under severe exposure or emergency conditions, wear acid-resistant clothing and boots.

8.2.2.4 Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Section 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties9.1.1 Appearance

Color: Bluish gray metal Odor: Odorless Odor threshold: No Data

9.1.2 Safety relevant basic data pH (20 °C): No Data Melting point/range(°C): 252.2222-360 Initial boiling point/range (°C): 1380 Decomposition temperature (°C): No Data Flash point (°C): No Data Ignition temperature (°C): No Data

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

9.2

Revision date: February 13, 2014

Page 7 of 19

Vapor pressure (hPa): No Data Vapor density (air = 1): No Data Density (g/cm3): 599.3267-705.4575 lbs/ft³ Bulk density (kg/m3): No Data Specific Gravity/Relative Density (Water=1): 9.6-11.3 Water solubility (20°C in g/l): No Data Solubility(ies): No Data Partition coefficient: No Data N-Octanol/Water (log Po/w): No Data Viscosity, dynamic (mPa s): No Data

Other safety information: Properties of explosive atmospheres (mixtures): Gases and vapors: No Data Dusts: No Data Physical chemical properties of nanoparticles: No Data Limiting oxygen concentration: No Data Bulk density: No Data Solubility in different media: No Data Stability in organic solvents and identity of relevant degradation products: No Data Evaporation rate: No Data Conductivity: No Data Surface tension: No Data Dissociation constant in water (pKa): No Data Oxidation-reduction Potential: No Data Fat solubility (solvent - oil to be specified): No Data Critical temperature: No Data

Section 10: Stability and reactivity

10.1	Reactivity:	
	Not reactive	
10.2	Chemical stability:	
	Stable under normal temp	peratures and pressures
10.3	Possibility of hazardous r	eactions
	Hazardous polymerizatio	n will not occur.
10.4	Conditions to avoid:	
	Prolonged overcharge, so	urces of ignition.
10.5	Incompatible materials:	
	Avoid contact with strong	bases, acids, combustible organic materials, halides, halogenates, potassium
	nitrate, permanganate, per	roxides, nascent hydrogen, reducing agents and water.
10.6	Hazardous decomposition	n products:
	Lead compounds exposed	to high temperatures will likely produce toxic metal fume, vapor or dust; contact
	with strong acid/base or p	resence of nascent hydrogen may generate highly toxic arsine gas.

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 8 of 19

Section 11: Toxicological Information							
11.1 Information on toxicological effects:							
Lead (7439-92-1)	Effect dose /	Species	Method	Time			
Acute oral toxicity	155 mg/kg	Human	LDLo				
Acute oral toxicity	1050 ug/kg	Rat	TDLo	30 Weeks(int.)			
Acute inhalative toxicity (dust/mist)	0.011 mg/m3	Human	LCLo	26 Weeks (int.)			
Mutagen	23 ug/m3	Rat	Inhalation	16 Weeks			
Reproductive	790 mg/kg	Rat	TDLo (Oral)	1			
Reproductive	3 mg/m3	Rat	TCLo	1-21 Days preg.			
	, i i i i i i i i i i i i i i i i i i i		(Inhalation)				
Antimony (7440-36-0)	Effect dose /	Species	Method	Time			
•	Concentration	-					
Acute oral toxicity	100 mg/kg	Rat	LD50	1			
Acute inhalative toxicity (dust/mist)	13.5 mg/m3	Human	LCLo	4 Hours			
Tumorigen/Carcinogen	50 mg/m3	Rat	TCLo	7 hours 52 weeks			
		1 1 1	1 1 1 1	(int.)			
Arsenic (7440-38-2)	Effect dose /	Species	Method	Time			
	Concentration	1					
Acute oral toxicity	763 mg/kg	Rat	LD50				
Acute oral toxicity	5 mg/kg	Rat	LDLo				
Mutagen	0.211 mg/L	Human	Oral	15 Years			
Reproductive	605 ug/kg	Rat	TDLo	35 weeks preg.			
11.2 Other information:				· · · · · ·			

11.2 Other information: 11.2.1 Carcinogenic Effects:

Material is an article. No health effects are expected related to normal use of this product as sold. Material does contain components that exhibit carcinogenic effects.

Carcinogenic Effects					
	CAS	IARC	NTP		
Lead	7439-92-1	Group 2A–Probable Carcinogen	Reasonably anticipated to be human carcinogen		

- 11.2.2 Routes of exposure:
- 11.2.2.1 In case of ingestion:

Acute (Immediate): Under normal conditions of use, no health effects are expected. Lead ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping.

- Chronic (Delayed): No data available
- 11.2.2.2 In case of skin contact:

Acute (Immediate): Under normal conditions of use, no health effects are expected.

Chronic (Delayed): No data available

11.2.2.3 In case of inhalation:

Acute (Immediate): Under normal conditions of use, no health effects are expected. Contents of an open battery can cause respiratory irritation.

Chronic (Delayed): Repeated and prolonged exposure may cause irritation.

11.2.2.4 In case of eye contact:

Acute (Immediate): Under normal conditions of use, no health effects are expected. Exposure to dust may cause irritation.

Chronic (Delayed): No data available

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 9 of 19

			Section 12: Ecolo	ogical information	on		
12.1	Toxicity:						
12.1.1	Aquatic toxicity Substances						
12.1.1		ort-term) toxicity:	No Data				
Effect d		Exposure time	Species	Method	Evaluation	Remark	
Persiste	nce/Degrad	lability: Lead is pe	rsistent in soils and s	ediments			
1 01 51510	nee/Degrae	daonity. Lead is pe	isistent in sons and s	ediments.			
			Section 13: Dispo	sal consideratio	ins		
13.1	Waste tre	atment methods	cetton 15. Dispu		115	1	
13.1.1		ackaging disposal:					
	Dispose of	of content and/or co	ontainer in accordance	e with local, regiona	l, national, and/or in	ternational	
	regulation						
13.1.2	Waste co 16 06 05	des/waste designat	ions according to EW	C/AVV:			
13.2		al information:					
13.2			sterisk (*) is conside	red as a hazardous w	vaste pursuant to Dir	rective	
			aste, and subject to t				
	Directive	applies.					
			Section 14: Tran		on		
1 4 1			tteries is Not Regulat	ed			
14.1		sport (CFR 49: DC	or) is as defined by 49CI	EP 172 101 by the U	S. Doportmont of T	rongnortation	
	UN-No:		is as defined by 49Cl	rk 172.101 by the O	.S. Department of T	ransportation	
		ipping name:					
	Class(es):						
	Packing g						
	Hazard la						
	Special p	rovision(s)/Excepti	ions:				
14.2	Land tran	sport (ADR/RID/C	GVSEB):				
			by the United Natio	ns Economic Comm	ission for Europe to	be dangerous	
1	goods.				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	
	UN-No:						
	-	ipping name:					
	Class(es):						
	Packing g	ation Code:				The second se	
	Hazard la				the state of the		
		rovision(s):					
	1 · · · F						

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 10 of 19

Land transport (TDG):

This product is not classified as dangerous goods by the TDG standards UN-No: Proper shipping name: Class(es): Packing group: Hazard label(s): Special provision(s):

14.3 Sea transport (IMDG-Code/GGVSee):

This product is not classified as dangerous goods by the IMO UN No: Proper shipping name: Class(es): Packing group: Marine Pollutant: Special provision(s):

14.4 Air transport (ICAO-IATA/DGR):

This product is not classified as dangerous goods by the International Air Transport Association (IATA) or the ICAO.

UN No: Proper shipping name: Class(es): Packing group: Special provision(s):

Section 15: Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation specific for the mixture
- 15.1.1 National regulations(Canada):

WHMIS Classification: This product does not meet the classification criteria of the Controlled Products Regulations. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the Controlled Products Regulations.

Canada DSL:

The following substances are listed on the Canadian DSL:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

Canada NDSL:

None of the components on this SDS are listed on the Canadian NDSL:

WHMIS:

Ingredient Disclosure List

ingreatent Discrosure List					
Substance	CAS No.	Wt %	Disclosure Limit %		
Calcium	7440-70-2	0.002%	Not Listed		
Lead	7439-92-1	89-92%	0.1%		
Lead as Lead compounds		89-92%	Not Listed		
Lead as Lead, inorganic		89-92%	1%		
compounds					
Tin	7440-31-5	0.006%	1%		
Antimony	7440-36-0	0.2 %	1%		

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 11 of 19

Antimony as Antimony compounds		0.2%	1%
Arsenic	7440-38-2	0.003%	0.1%

CEPA:

Priority Substances List					
Substance	CAS No.	Wt %	Status		
Calcium	7440-70-2	0.002%	Not Listed		
Lead	7439-92-1	89-92%	Not Listed		
Lead as Lead compounds		89-92%	Not Listed		
Lead as Lead, inorganic		89-92%	Not Listed		
compounds					
Tin	7440-31-5	0.006%	Not Listed		
Antimony	7440-36-0	0.2 %	Not Listed		
Antimony as Antimony		0.2%	Not Listed		
compounds					
Arsenic	7440-38-2	0.003%	Not Listed		

15.1.2 National regulations(China):

The following components are listed on the Inventory list for China: Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

15.1.3 National regulations(European Union): Classification:

- Class
- Xi
- Risk Phrases:

R36, R38

Safety Phrases:

\$1/2, \$26, \$30, \$45

The following components are listed on the EU EINECS:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

None of the above mentioned components are listed on the EU ELNICS.

Substance	CAS	WT %	Concentration Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	2.5%<=C: Repr. Cat. 3; R62 1%<=C: Xn; R20/22
			0.5%<=C: R33
Lead as Lead, inorganic		89-92	Not Listed
compounds		10	
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony		0.2	0.25%<=C: Xn; R20/22
compounds			
Arsenic	7440-38-2	0.003	Not Listed

CLP (1272/2008) Concentration Limits

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 12 of 19

Substance	CAS	WT %	Substances and Preparations
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	A, E, 1(except those specified elsewhere in the annex)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	A, 1 (except tetroxide, pentoxide, trisulphide, pentasulphide and
			those specified elsewhere in the annex)
Arsenic	7440-38-2	0.003	Not Listed

Germany

Lead Restrictions:

Lead concentration in the blood above 300 μ g/L in male employees and 100 μ g/L in female employees requires additional training for personal hygiene and vigilance. Lead concentration in the blood above 350 μ g/L in male employees and 200 μ g/L in female employees requires additional training for personal hygiene and vigilance; Lead concentration in the blood above 400 μ g/L in male employees and 300 μ g/L in female employees requires additional training for personal hygiene and vigilance; See TRGS 505 for detailed regulations regarding lead and lead compounds.

Employment restrictions for employees below the age of 18 years; Employment restrictions for pregnant or breastfeeding women; Prohibited for use at home based workplaces; Restrictions apply for use of lead compounds in packaging material, drinking water systems, cars, electrical and electronical devices; See TRGS 505 for detailed regulations regarding lead and lead compounds.

Emission Limits for		1	
Substance	CAS	WT %	Emission Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439 <mark>-92</mark> -1	89-92	2.5 g/h Mass flow (class II); 0.5 mg/m3 mass
			concentration (Class II)
Lead as Lead compounds		89-92	2.5 m/h Mass flow (Class II, as Pb); 0.5 mg/m3
			Mass concentration (Class II, as Pb)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	5 g/h Mass flow (Class III); 1 mg/m3 Mass
			concentration (Class III)
Antimony	7440-36-0	0.2	5 g/h Mass flow (Class III); 1 mg/m3 Mass
			concentration (Class III)
Antimony as Antimony compounds		0.2	5 g/h Mass flow (Class III, as Sb); 1 mg/m3 Mass
			concentration (Class III, as Sb)
Arsenic	7440-38-2	0.003	Not Listed

Emission Limits for Inorganic Dusts

15.1.4 National regulations(Japan):

The following chemicals are on the Japanese ENCS:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 13 of 19

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	0.1% weight
Lead as Lead compounds		89-92	0.1% weight
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	0.1% weight

ISHL Prevention of Lead Poisoning

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

ISHL Notifiable Substances

ISTIE I (outifuote Substances			
Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	0.1% weight
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	0.1% weight
Tin	7440-31-5	0.006	0.1% weight
Antimony	7440-36-0	0.2	0.1% weight
Antimony as Antimony compounds		0.2	0.1% weight
Arsenic	7440-38-2	0.003	0.1% weight

Air Pollution Control Law: Emission Standards for Air Pollutants

Substance	CAS	WT %	Emission Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	16-20 mg/Nm3
Lead as Lead compounds		89-92	16-20 mg/Nm3
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds	1 9 m.M	0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 14 of 19

Pollutant Release Transfer Register (PRTR): Class 1 Substances

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	304
Lead as Lead compounds		89-92	305 (Designated class 1 substance)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	31
Antimony as Antimony compounds		0.2	31
Arsenic	7440-38-2	0.003	332 (Designated class 1 substance)

ISHL Working Environment Evaluation Standards: Administrative Control Levels

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	0.05 mg/m3 ACL
Lead as Lead compounds		89-92	0.05 mg/m3 ACL (as Pb)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	0.003 mg/m3 ACL

15.1.5 National regulations(Korea):

The following substances are listed on the Korean KECL:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

15.1.6National regulations(Mexico):

Pollutant Release and Transfer Register: Reporting Emissions

Substance	CAS	WT %	Threshold Quantities
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	1 kg/yr TQ
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	1 kg/yr TQ

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 15 of 19

15.1.7 National regulations(United States):

The following substances are on the MA, NJ, and PA Right To Know Lists: Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

The following substances are on the TSCA inventory:

Lead (7439-92-1); Antimony (7440-36-0); Tin (7440-31-5); Arsenic (7440-38-2); Calcium (7440-70-2)

OSHA: Specifically Regulated Chemicals

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	30 µg/m3 Action Level (Poison, See 29 CFR
			1910.1025); 50 µg/m3 TWA
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	30 µg/m3 Action Level (Poison, See 29 CFR
			1910.1025, as Pb); 50 μg/m3 TWA (as Pb)
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

CAA: 1990 Hazardous Air Pollutants

Substance	CAS	WT %	Limit
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	(includes any unique chemical substance that
			contains Lead as part of its infrastructure)
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	(includes any unique chemical substance that
			contains Antimony as part of its infrastructure)
Arsenic	7440-38-2	0.003	Not Listed

CERCLA/SARA

LA/SAKA Hazardous Substances and Their Reportable Quantities

Substance	CAS	WT %	Reportable Quantity
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	10 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers); 4.54 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers)
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 16 of 19

Antimony	7440-36-0	0.2	5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers)
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	1 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers); 0.454 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is larger than 100 micrometers)

Section 302 Extremely Hazardous Substances EPCRA RQs

Substance	CAS	WT %	Reportable Quantity
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds	1 1 1	89-92	Not Listed
Lead as Lead, inorganic compounds	N L L	89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

Section 302 Extremely Hazardous Substances TPQs

Substance	CAS	WT %	Threshold Planning Quantity
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Not Listed

RCRA

Basis for Listing: Appendix VII

Dasis for Listing: A	spendix vII	14	
Substance	CAS	WT %	Basis
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Included in waste streams: F035, F037, F038, F039, K002, K003, K005, K046, K048, K049, K051, K052, K061, K062, K064, K065, K066, K069, K086, K100, K176
Lead as Lead compounds	0 8 8	89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Included in waste streams: F039, K021, K161, K177
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	Included in waste streams: F032, F034, F035, F039, K031, K060, K084, K101, K102, K161, K171, K172, K176

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 17 of 19

D Series Wastes: Max Concentration of Contaminants for the Toxic Characteristic

Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	5.0 mg/L
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds		0.2	Not Listed
Arsenic	7440-38-2	0.003	5.0 mg/L

Hazardous Constituents: Appendix VIII to 40 CFR 261

Substance	CAS	WT %	Status
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Hazardous constituent – no waste number
Lead as Lead compounds		89-92	Hazardous constituent – no waste number
Lead as Lead, inorganic compounds	10 M	89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Hazardous constituent – no waste number
Antimony as Antimony compounds		0.2	Hazardous constituent – no waste number
Arsenic	7440-38-2	0.003	Hazardous constituent – no waste number

California: California Proposition 65

Substance	CAS	WT %	Status	
Calcium	7440-70-2	0.002	Not Listed	
Lead	7439-92-1	89-92	Carcinogen(initial date 10/1/92); developmental toxicity(initial date 2/27/87); 0.5 µg/day(Maximum Allowable Dose Level); 15 µg/day oral(No Significant Risk Level); female reproductive toxicity(initial date 2/27/87); male reproductive toxicity(initial date 2/27/87)	
Lead as Lead compounds		89-92	Carcinogen(initial date 10/1/92)	
Lead as Lead, inorganic compounds		89-92	Developmental toxicity(initial date 2/27/87)	
Tin	7440-31-5	0.006	Not Listed	
Antimony	7440-36-0	0.2	Not Listed	
Antimony as Antimony compounds	N. Printer	0.2	Not Listed	
Arsenic	7440-38-2	0.003	0.06µg/day inhalation(No Significant Risk Level); 10µg/day except inhalation(No Significant Risk Level)	

Pennsylvania

Environmental Haza	rd list	1000000	
Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	
Lead as Lead compounds		89-92	
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	
Antimony as Antimony compounds		0.2	
Arsenic	7440-38-2	0.003	

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 18 of 19

1101131011	uaic.	•	condary	10, 2

Special hazardous Substances

Substance	CAS	WT %	Regulatory Level
Calcium	7440-70-2	0.002	Not Listed
Lead	7439-92-1	89-92	Not Listed
Lead as Lead compounds		89-92	Not Listed
Lead as Lead, inorganic compounds		89-92	Not Listed
Tin	7440-31-5	0.006	Not Listed
Antimony	7440-36-0	0.2	Not Listed
Antimony as Antimony compounds	1.5	0.2	Not Listed
Arsenic	7440-38-2	0.003	

Rhode Island: Hazardous Substances List

CAS	WT %	Regulatory Level
7440-70-2	0.002	Flammable
7439-92-1	89-92	Toxic (dust and fume)
and the second	89-92	Not Listed
	89-92	Not Listed
7440-31-5	0.006	Toxic
7440-36-0	0.2	Toxic
	0.2	Toxic
7440-38-2	0.003	Toxic; Carcinogen
	7440-70-2 7439-92-1 7440-31-5 7440-36-0	7440-70-2 0.002 7439-92-1 89-92 89-92 89-92 7440-31-5 0.006 7440-36-0 0.2 0.2 0.2

Section 16: Other Information

16.1	Relevant R-, H- and EUH-phrases (number and full text):
	Hazard Abbreviations:
	Xi: Irritant
	Xn: Harmful
	N: Dangerous for the environment
	T: Toxic
	F: Highly Flammable
	Risk Phrases:
	R15: Contact with water liberates extremely flammable gases
	R20/22: Harmful by inhalation and if swallowed
	R23/25: Toxic by inhalation and if swallowed
	R33: Danger of cumulative effects
	R36: Irritating to eyes
1.1	R38: Irritating to skin
	R50: Very toxic to aquatic organisms
	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment R53: May cause long-term adverse effects in the aquatic environment
	R61: May cause harm to the unborn child
	R62: Possible risk of impaired fertility
	Safety Phrases:
	S1/2: Keep locked up and out of the reach of children
	S2: Keep out of the reach of children
	S8: Keep container dry
	S20/21: When using do not eat, drink, or smoke
	S24/25: Avoid contact with skin and eyes
	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
	S28: After contact with skin, wash immediately with plenty of water

Trade name: Dry Charge Battery SDS No: 853021 Print date: February 13, 2014

Revision date: February 13, 2014

Page 19 of 19

S30: Never add water to this product
S43: In case of fire use CO2, dry chemical, or foam. Never use water
S45: In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)
S53: Avoid exposure – obtain special instructions before use
S60: This material and its container must be disposed of as hazardous waste
S61: Avoid release to the environment. Refer to special instructions/safety data sheet
Hazard statements:
H313: May be harmful in contact with skin
H315: Causes skin irritation
H335: May cause respiratory irritation
EUH201A: Warning! Contains lead
Precautionary statements:
P102: Keep out of reach of children.
P233: Keep containers tightly closed.
P210: Keep away from heat, sparks, and open flame while charging batteries.

16.2 Further information:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Yuasa, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Yuasa, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

